

STYACRYL PS 25

Paper Polymer Emulsion

Version: 2.1/ 2015

TDS EU/EN

Characteristic

Styacryl PS 25 is surface sizing agent for paper and board based on modified styrene - acrylate copolymer.

Application

- △ Surface sizing agent for paper and board
- △ Surface smoothing
- △ Improvement of printability
- △ Prevents crinkling

Usage

- Styacryl PS25 generally applied with starch. Addition into starch solution may be in the starch tank or into pipeline, before or after starch supply pump.
- Styacryl PS25 is compatible with many chemicals, like dyes, brighteners, etc.
- Styacryl PS25 is resistant to cationic strongly acids. Will not harmed by a reduction in PH.
- Styacryl PS25 consumption is depends on type and degree of sizing of the base paper, sizing requirements, etc. In general 0.2 – 0.5 g/m² of paper sufficient.

Packing

Available in 200 l PE drums, IBC's or bulk

Technical Data

<u>Appearance</u>	Milky white emulsion
<u>Stabilization</u>	Slightly anionic
<u>Odor</u>	Weakly
<u>PH</u> DIN ISO 976	6.0 ± 1
Solids Content (%) (DIN ISO 1624, 2h - 105C)	27 ± 1
<u>Viscosity</u> DIN ISO 2555 Brookfield Spindle 1/100	≤ 100 mPa.s
<u>Density</u> 20 °C, DIN EN 2811-1	approx. 1.04 g/cm ³
Storage stability	Protect from freezing and direct sunlight at 5°C to 25°C for no longer of one year

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. However, we do not assume any liability whatsoever for the accuracy or completeness of the information herein. It should therefore not be construed as an expressed or implied warranty of specific properties of the products or the suitability for a particular use. Any existing industrial property rights must be observed. The quality of our products is governed by our General Conditions of Sale. In every case we urge and recommend that purchasers before using any product in full-scale production make their own test to determine to their own satisfaction whether the product is of acceptable quality and is suitable for their particular purposes under their own operating conditions