



### Vinyl Acetate

Molecular formula: C<sub>4</sub>H<sub>6</sub>O<sub>2</sub>

CAS № 108-05-4

EINECS № 203-545-4

INDEX № 607-023-00-0

Characteristic	Limit	Value	Method
Vinyl Acetate	Min. 99.9	% (w/w)	Газова хроматография
Aldehydes as Acetaldehyde	Max. 0.010	% (w/w)	Газова хроматография
Water	Max. 0.04	% (w/w)	DIN 51 777/ ASTM 1364 (mod. Karl-Fischer-Method)
Acidity as Acetic Acid	Max. 0.005	% (w/w)	DIN EN ISO 2114/ ASTM D 1613 or ASTM D 2086
Platinum/Cobalt Color (Hazen/APHA Color)	Max. 5		DIN EN 1557/ DIN ISO 6271/ ASTM D 1209
Specific gravity at 20 °C	0.933 – 0.935		DIN EN 51757/ Method D/ ASTM D 4052

#### **Remarks:**

<sup>1</sup>Product conforms to limit, but test is not routinely performed.

Version № 1

Version Released: 01 January 2013

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should therefore not be construed as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.