

5.12.2013

# SUPERFLOC® A-100 HMW series

## Anionic Dry PAMs

The Kemira Superfloc A-100 HMW series are highly effective high molecular weight anionic flocculants. They condition solids for dewatering operations and aid water clarification processes in various industries. They show exceptional performance in liquid-solid separations in a wide range of conditions.

### Applications

These products may be beneficial in any liquid-solid separation process. They are especially recommended for:

- Dissolved air flotation
- Filtration
- Gravity settling
- Mechanical dewatering
- Phosphorus removal

### Benefits

- Dry product minimizes storage requirements
- Economical to use – effective at low dosage levels
- Effective high solids removal
- Effective over a wide range of pH; does not alter the system pH
- Eliminates or reduces use of inorganic salts
- High storage stability
- Fast settling rates.

### Health and Safety

Before handling these materials read the corresponding Kemira Material Safety Data Sheets (MSDS) for safety and health data.

For chemical inventory regulatory control listing information, see the MSDS.

### Handling and Storage

Solutions are no more corrosive than water. Recommended materials of construction include stainless steel, fibreglass, plastic, and glass or epoxy-lined vessels. Do not use iron, copper or aluminum. The shelf life of these products is 24 months when stored in unopened packages in a dry atmosphere at temperatures no higher than 40°C/104°F.

Spilled polymer is very slippery and should be absorbed onto an inert material and collected prior to thoroughly flushing with water.

### Product Addition

Stock solutions can be prepared up to 0.5 % concentration via an automated make down unit or on a batch basis. Solutions should be aged 30-60 minutes for maximum effectiveness. High quality make up water should be used. Secondary dilution water should be added to the stock solution prior to the addition point at a ratio up to 10:1. Centrifugal pumps should be avoided for polymer transfer.

#### Kemira Oyj

P.O.Box 330 (Porkkalankatu 3)  
FI-00101 Helsinki  
Finland  
[www.kemira.com](http://www.kemira.com)

Europe, Middle-East and Africa  
Tel +358 10 8611  
North America  
Tel +1 770 436 1542

South America  
Tel +55 11 2189 4900  
Asia-Pacific  
Tel +86 21 6037 5999

5.12.2013

## Delivery

The Superfloc A-100 HMW series products are delivered in 25 kg & 750 kg moisture-resistant bags. Other pack sizes may be available on request.

## Regulatory Approvals

These products may conform to certain regulatory requirements. Please contact your Kemira sales representative for more details, or refer to the appropriate regulatory information sheet.

## Product Properties

	A-100HMW	A-110HMW	A-115HMW	A-120HMW	A-130HMW	A-137HMW	A-150HMW
Chemical Type	Anionic Polyacrylamide						
Appearance	Off-white, Granular Powder						
Relative Charge	Low	Low	Low - Med	Medium	Medium	Med – High	High
Molecular weight	Very High	Very High	Very High	Very High	Very High	Very High	Very High
Bulk Density (kg/litre)	0.78	0.80	0.81	0.82	0.83	0.85	0.90
pH of 0.5% solution (25°C)	7.0 – 9.0						
Viscosity @ 25°C (cp / mPa.sec)							
0.10%	130	200	220	230	250	250	300
0.25%	330	400	500	500	550	600	600
0.50%	800	950	1000	1000	1100	1100	1200

### Kemira Oyj

P.O.Box 330 (Porkkalankatu 3)  
FI-00101 Helsinki  
Finland  
www.kemira.com

Europe, Middle-East and Africa  
Tel +358 10 8611  
North America  
Tel +1 770 436 1542

South America  
Tel +55 11 2189 4900  
Asia-Pacific  
Tel +86 21 6037 5999